

(19)日本国特許庁 (J P)

(12)公表特許公報 (A)

(11)特許出願公表番号

特表平10-510158

(43)公表日 平成10年(1998)10月6日

(51)Int.Cl. ⁸		識別記号	F 1	
C 1 2 M	1/00		C 1 2 M	1/00 Z
B 0 3 C	1/25		B 0 3 C	1/25
C 1 2 N	15/00		C 1 2 Q	1/00 A
C 1 2 Q	1/05		C 1 2 N	15/00 A
審査請求 未請求 予備審査請求 有 (全 48 頁)				
(61)出願番号	特願平8-517831		(71)出願人	ガスラ・バイオサイエンス・コーポレーション
(65) (22)出願日	平成7年(1995)12月6日			アメリカ合衆国02155マサチューセッツ州
(65) 翻訳文提出日	平成9年(1997)6月9日			メッドフォード、ボストン・アベニュー
(69)国際出願番号	P C T / U S 9 8 / 1 6 2 5 6			200番
(67)国際公開番号	W O 9 8 / 1 7 9 5 9		(72)発明者	マイアン, アレック
(67)国際公開日	平成8年(1996)6月13日			アメリカ合衆国02139マサチューセッツ州
(61)優先権主張番号	0 8 / 3 5 3, 5 7 3			ケンブリッジ、マガジン・ストリート
(62)優先日	1964年12月9日			137番
(63)優先権主張国	米国 (U S)		(74)代理人	弁理士 青山 薫 (外 2 名)


最終頁に続く

(54)【発明の名称】 電気サイクル反応を行うための装置

(57)【要約】

本発明は、電磁場による核酸鎖の分離に基づいて、特定の核酸配列の増幅方法を行うための装置を提供する。この分離手段は、増幅方法における伸縮ポリヌクレオチドの使用を可能とし、それによって、その増幅方法の速度および正確さ、さらにはまた、増幅することができる核酸の大きさをも増大させる。

Figure 2A



* NOTICES *

JPO and INPIT are not responsible for any damages caused by the use of this translation.

1.This document has been translated by computer. So the translation may not reflect the original precisely.

2.*** shows the word which can not be translated.

3.In the drawings, any words are not translated.

CLAIMS

[Claim(s)]

1. It is a device for performing a magnetic cycle reaction, (a) A temperature control means of a temperature control sample block (some magnetic cycle reaction sample tubes are attached in sample tube WERU) containing a plate containing sample tube WERU of a large number located in a line in a row, and a sample block;
- (b) The 1st magnetism element and its 1st magnetism element are located a sample block top and near it, A flow of current which passes along a wire which the 1st magnetism element contains a coil of a large number located in a line in a row, and the coil contains an electrical conduction wire of many volumes in the surroundings of an elasticity iron core, and contains the coil produces a magnetic field around the 1st magnetism element,;
- (c) The 2nd magnetism element and its 2nd magnetism element are located the bottom of a sample block, and near it, A flow of current which passes along a wire which the 2nd magnetism element contains a coil of a large number located in a line in a row, and the coil contains an electrical conduction wire of many volumes in the surroundings of an elasticity iron core, and contains the coil produces a magnetic field around the 2nd magnetism element,;
- A control device containing a microprocessor and its control device (d) A temperature control sample block, And it is connected effective in each of the 1st magnetism element and the 2nd magnetism element, The control device is connected effective also in a user interface again, A device included combining a power supply which the control device is connected effective in; and the (e) control device which control a flow of current which passes along each magnetic element, and temperature of a temperature control sample block, and supplies electric power to a device.
2. Use the device according to claim 1, it is how to perform a magnetic cycle reaction for amplifying a specific DNA fragment, include (a) solid phase primer in a nucleic acid chain complementary to target nucleic acid, and make a solid phase chain combined with target nucleic acid,;
- (b) Separate a solid phase chain and target nucleic acid,;
- (c) Include a magnetic primer in a nucleic acid chain complementary to a solid phase chain, and obtain a double chain which has one solid phase chain and one magnetic chain,;
- (d) Separate a solid phase chain from a magnetic chain by applying an electromagnetic field of sufficient intensity to dissociate a double chain by generating a magnetic field in the 1st magnetism element of the device according to claim 1,;
- (e) Make a solid phase chain anneal a magnetic primer complementary to a solid phase chain, and make a magnetic chain anneal a complementary solid phase primer to a magnetic chain by applying an electromagnetic field by generating a magnetic field in the 2nd magnetism element of the device according to claim 1,;
- (f) A way only the number of times required to elongate an annealed primer by suitable DNA polymerase, and obtain amplification DNA of quantity of; and the (g) request includes repeating a process of (d) - (f).

3. Use the device according to claim 1, it is a method for amplifying specific single strand target nucleic acid, include (a) magnetism primer in a nucleic acid chain complementary to target nucleic acid, and make a magnetic chain combined with target nucleic acid;
- (b) Separate a magnetic chain and target nucleic acid;
- (c) Include a solid phase primer in a nucleic acid chain complementary to a magnetic chain, and obtain a double chain which has one solid phase chain and one magnetic chain;
- (d) Separate a solid phase chain from a magnetic chain by applying an electromagnetic field of sufficient intensity to dissociate a double chain by generating a magnetic field in the 1st magnetism element of the device according to claim 1;
- (e) Make a solid phase chain anneal a magnetic primer complementary to a solid phase chain, and make a magnetic chain anneal a complementary solid phase primer to a magnetic chain by generating a magnetic field in the 2nd magnetism element of the device according to claim 1;
- (f) A way only the number of times required to elongate an annealed primer by suitable DNA polymerase, and obtain amplification DNA of quantity of; and the (g) request includes a process of repeating a process of (d) - (f).
4. Use the device according to claim 1, it is a method for amplifying specific double strand target nucleic acid, separate a chain of (a) target nucleic acid, and obtain the 1st chain and 2nd chain;
- (b) Include a solid phase primer in a chain complementary to the 1st chain, obtain the 1st heteroduplex that has the 1st chain and solid phase chain, and include a magnetic primer in a chain complementary to the 2nd chain, and obtain the 2nd heteroduplex that has the 2nd chain and magnetic chain;
- (c) Separate the 1st heteroduplex and 2nd heteroduplex;
- (d) Make a solid phase chain anneal a magnetic primer complementary to a solid phase chain, and make a magnetic chain anneal a complementary solid phase primer to a magnetic chain;
- (f) elongating an annealed primer by suitable DNA polymerase —; and (g) — separating a solid phase chain from a magnetic chain by applying an electromagnetic field of sufficient intensity to dissociate a double chain by generating a magnetic field in the 1st magnetism element of the device according to claim 1 —;
- (h) Make a solid phase chain anneal a magnetic primer complementary to a solid phase chain, and make a magnetic chain anneal a complementary solid phase primer to a magnetic chain by generating a magnetic field in the 2nd magnetism element of the device according to claim 1;
- (i) A way only the number of times required to elongate an annealed primer by suitable DNA polymerase, and obtain amplification DNA of quantity of; and the (j) request includes a process of repeating a process of (g) - (i).

[Translation done.]